

# PIN RECEPTACLES

FOR 0,64 - 0,94 DIAMETER PINS AND 0,64 SQUARE PINS

<p><b>1305</b> 1305-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p><b>1306</b> 1306-0-15-XX-47-XX-04-0 Press-fit in 1,55 mounting hole</p>	<p><b>7305</b> 7305-0-15-XX-47-XX-10-0 Solder mount in 1,52 min. mounting hole Also available on 8mm wide carrier tape: 6,000 parts per 330mm reel See page 194.9 for Tape &amp; Reel details</p>	<p><b>0400</b> 0400-0-15-XX-47-XX-04-0 Press-fit in 1,7 mounting hole</p>
<p><b>0335</b> 0335-0-15-XX-47-XX-04-0 Hex press-fit in 1,63 plated through-hole</p>	<p><b>4614</b> 4614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 1,52 → 2,54 thick board</p>	<p><b>4615</b> 4615-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 2,29 → 3,30 thick board</p>	<p><b>7614</b> 7614-0-31-XX-47-XX-04-0 Compliant press-fit in 1,02 ± 0,08 plated hole. For 1,52 → 2,54 thick board</p>
<p><b>8401</b> 8401-0-15-XX-47-XX-04-0 Hex press-fit in 1,6 plated through-hole</p>	<p><b>2400</b> 2400-0-15-XX-47-XX-04-0 Press-fit in 1,68 mounting hole</p>	<p><b>6857</b> 6857-0-15-XX-47-XX-10-0 Press-fit in 1,55 mounting hole</p>	<p><b>9393</b> 9393-0-15-XX-47-XX-10-0 Press-fit in 1,70 mounting hole</p>

## SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Millimeters

**Tolerances On:** Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



**ORDER CODE:** XXXX - X - XX - XX - 47 - XX - XX - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#47 CONTACT (DATA ON PAGE 256)**

(For alternate contact choices, see group D on page 248)

