

PIN RECEPTACLES

FOR 1,22 - 1,63 DIAMETER PINS (#13 CONTACT)
FOR 1,14 - 1,65 DIAMETER PINS (#23 CONTACT)

<p>0364 0364-0-15-XX-13-XX-10-0 Solder mount in 2,54 min. mounting hole Also available on 16mm wide carrier tape: 1,300 parts per 330mm reel See page 194.13 for Tape & Reel details</p>	<p>0363 0363-0-15-XX-23-XX-10-0 Solder mount in 2,59 min. mounting hole</p>	<p>0365 0365-0-15-XX-23-XX-10-0 Hex press-fit in 2,67 plated through-hole Also available on 16mm wide carrier tape: 1,200 parts per 330mm reel See page 194.14 for Tape & Reel details</p>	<p>0366 0366-0-15-XX-13-XX-10-0 Press-fit in 2,77 mounting hole</p>
<p>0372 0372-0-15-XX-13-XX-10-0 Solder mount in 2,59 min. mounting hole Also available on 24mm wide carrier tape: 950 parts per 330mm reel See page 194.14 for Tape & Reel details</p>	<p>0362 0362-0-15-XX-X3-XX-10-0 Solder mount in 2,59 min. mounting hole</p>	<p>0367 0367-0-15-XX-23-XX-10-0 Square press-fit in 1,02 plated through-hole</p>	<p>9324 9324-0-15-XX-23-XX-04-0 Press-fit in 2,69 mounting hole</p>
<p>0492 0492-0-15-XX-13-XX-04-0 Press-fit in 2,69 mounting hole</p>	<p>0381 0381-0-15-XX-23-XX-10-0 Press-fit in 2,64 mounting hole</p>	<p>4034 4034-0-15-XX-23-XX-04-0 Press-fit in 2,77 mounting hole</p>	<p>3044 3044-0-15-XX-23-XX-04-0 Solder mount in 2,64 min. mounting hole</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

01 5,08µm TIN/LEAD OVER NICKEL

◆ 80 5,08µm TIN OVER NICKEL (RoHS)

◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

01 5,08µm TIN/LEAD OVER NICKEL

◆ 80 5,08µm TIN OVER NICKEL (RoHS)

◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#13 or #23 CONTACT (DATA ON PAGE 260)

(For alternate contact choices, see group G on page 248)

