

# PIN RECEPTACLES

**FOR 1,22 - 1,63 DIAMETER PINS (#13 CONTACT)  
FOR 1,14 - 1,65 DIAMETER PINS (#23 CONTACT)**

<p><b>8365</b> <b>8365-0-15-XX-13-XX-10-0</b> Hex press-fit in 2,69 plated through-hole</p>	<p><b>8996</b> <b>8996-0-31-XX-13-XX-04-0</b> Compliant press-fit in 1,02 ±0,08 plated hole. For 1,52 → 2,54 thick board</p>	<p><b>9064</b> <b>9064-0-15-XX-13-XX-10-0</b> Solder mount in 2,59 min. mounting hole Also available on 16mm wide carrier tape: 1,300 parts per 330mm reel See page 194.14 for Tape &amp; Reel details</p>	<p><b>9280</b> <b>9280-0-15-XX-13-XX-10-0</b> Solder mount in 2,59 min. mounting hole</p>
<p><b>8347</b> <b>8347-0-15-XX-13-XX-10-0</b> Solder mount in 2,77 min. mounting hole</p>	<p><b>4900</b> <b>4900-0-19-XX-23-XX-10-0</b> Swage mount in 1,70 hole</p>	<p><b>0716</b> <b>0716-0-33-XX-23-XX-10-0</b> Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.</p>	<p><b>0760</b> <b>0760-0-18-XX-13-XX-10-0</b> Press-fit in 2,69 mounting hole For wire sizes up to 16 AWG</p>

## SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Millimeters

**Tolerances On:** Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



**ORDER CODE:** XXXX - X - XX - XX - XX - XX - 0

**BASIC PART #** →

**SPECIFY SHELL FINISH:** →

01 5,08µm TIN/LEAD OVER NICKEL

◆ 80 5,08µm TIN OVER NICKEL (RoHS)

◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:** →

01 5,08µm TIN/LEAD OVER NICKEL

◆ 80 5,08µm TIN OVER NICKEL (RoHS)

◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

#13 or #23 CONTACT (DATA ON PAGE 260)

(For alternate contact choices, see group G on page 248)

