

PIN RECEPTACLES

FOR 0,38 - 0,56 DIAMETER PINS

<p>0512 0512-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0703 0703-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0574 0574-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0468 * 0468-0-15-XX-12-XX-04-0 Press-fit in 1,45 mounting hole</p>						
<p>8894 * 8894-0-15-XX-12-XX-10-0 Hex press-fit in 1,5 plated through-hole</p>	<p>0550 * 0550-0-15-XX-22-XX-10-0 Solder mount in 1,32 min. mounting hole Also available on 16mm wide carrier tape: 1,700 parts per 330mm reel See page 194.4 for Tape & Reel details</p>	<p>0671 * 0671-0-15-XX-12-XX-10-0 Solder mount in 1,6 min. mounting hole</p>	<p>0707 * 0707-0-15-XX-12-XX-10-0 Solder mount in 1,3 min. mounting hole</p>						
<p>5739 * 5739-0-18-XX-12-XX-10-0 Surface mount Also available on 16mm wide carrier tape: 3,000 parts per 330mm reel See page 194.4 for Tape & Reel details</p>		<p>1534 1534-X-15-XX-12-XX-04-0 Press-fit in 1,42 mounting hole</p>	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>1534-0</td> <td>2,41</td> </tr> <tr> <td>1534-1</td> <td>3,18</td> </tr> </tbody> </table>	Basic Part Number	Length A	1534-0	2,41	1534-1	3,18
Basic Part Number	Length A								
1534-0	2,41								
1534-1	3,18								

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: ±0,13
Diameters: ±0,051
Angles: ±2°

ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 02 2,54µm TIN/LEAD OVER NICKEL
- ◆ 84 2,54µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#12 or #22 CONTACT (DATA ON PAGE 252)

* (Contact may be interchanged with group B or C contact on page 248)

