

PIN RECEPTACLES

FOR 0,81 - 1,17 DIAMETER PINS

<p>8838 8838-0-15-XX-34-XX-10-0 Solder mount in 2,18 min. mounting hole</p>	<p>3100 3100-0-15-XX-34-XX-10-0 Solder mount in 1,88 min. mounting hole</p>	<p>8853 8853-0-15-XX-34-XX-10-0 Press-fit in 1,8 mounting hole</p>	<p>6800 6800-0-15-XX-34-XX-04-0 Solder mount in 2,03 min. mounting hole</p>
<p>0739 0739-0-15-XX-34-XX-10-0 Hex press-fit in 1,98 plated through-hole</p>	<p>8206 8206-0-15-XX-34-XX-40-0 Surface mount, board edge Also available on 16mm wide carrier tape: Packaged Vertically 1,400 parts per 330mm reel See page 194.14 for Tape & Reel details</p>	<p>P.C.B. Layout</p>	<p>0720 0720-0-33-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>
<p>4130 4130-0-33-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.</p>	<p>5084 5084-0-18-XX-34-XX-10-0 Press-fit in 2,06 mounting hole</p>	<p>0740 0740-0-18-XX-34-XX-10-0 Press-fit in 1,91 mounting hole For wire sizes up to 20 AWG</p>	<p>8731 8731-0-19-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Millimeters
Tolerances On: Lengths: ± 0,13
 Diameters: ± 0,051
 Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - 34 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#34 CONTACT (DATA ON PAGE 258)

(For alternate contact choices, see group E on page 248)

