

# PIN RECEPTACLES

**FOR 1,02 - 1,27 DIAMETER PINS (#02 CONTACT)**  
**FOR 1,02 - 1,52 DIAMETER PINS (#03 CONTACT)**

<p><b>0355</b>  <b>0355-0-15-XX-02-XX-10-0</b>          Solder mount in 2,59 min. mounting hole</p>	<p><b>0354</b>  <b>0354-0-15-XX-02-XX-10-0</b>          Pentagonal press-fit in 2,64 min. plated through-hole</p>	<p><b>3490</b>  <b>3490-0-15-XX-02-XX-10-0</b>          Press-fit in 2,31 mounting hole</p>	<p><b>3808</b>  <b>3808-0-15-XX-02-XX-10-0</b>          Press-fit in 2,29 mounting hole</p>
<p><b>9184</b>  <b>9184-0-15-XX-02-XX-40-0</b>          Bottom entry, surface mount          2,34 min. plated through-hole          Also available on carrier tape,          See page 194.16 for Tape &amp; Reel details</p>	<p><b>9222</b>  <b>9222-2-15-XX-02-XX-40-0</b>          Bottom entry, surface mount          2,08 min. plated through-hole          Also available on carrier tape,          See page 194.16 for Tape &amp; Reel details</p>	<p><b>4064</b>  <b>4064-0-18-XX-03-XX-40-0</b>          Surface mount          Also available on 16mm wide carrier tape:          2,400 parts per 330mm reel          See page 194.17 for Tape &amp; Reel details</p>	

**SPECIFICATIONS:**

**Shell Material:** Brass Alloy 360, 1/2 Hard  
**Contact Material:** Beryllium Copper Alloy 172, HT  
**Dimensions:** Millimeters  
**Tolerances On:** Lengths: ± 0,13  
 Diameters: ± 0,051  
 Angles: ± 2°



**ORDER CODE:** XXXX - X - XX - XX - 02 - XX - XX - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#02 or #03 CONTACT (DATA ON PAGE 259)**  
 (For alternate contact choices, see group F on page 248)

