

# PIN RECEPTACLES

**FOR 1,22 - 1,63 DIAMETER PINS (#13 CONTACT)**  
**FOR 1,14 - 1,65 DIAMETER PINS (#23 CONTACT)**

<p><b>8365</b>  <b>8365-0-15-XX-13-XX-10-0</b>  Hex press-fit in 2,69 plated through-hole</p>	<p><b>8996</b>  <b>8996-0-31-XX-13-XX-04-0</b>  Compliant press-fit in 1,02 ±0,08 plated hole. For 1,52 → 2,54 thick board</p>	<p><b>9064</b>  <b>9064-0-15-XX-13-XX-10-0</b>  Solder mount in 2,59 min. mounting hole  Also available on 16mm wide carrier tape:  1,300 parts per 330mm reel  See page 194.17 for Tape &amp; Reel details</p>	<p><b>9280</b>  <b>9280-0-15-XX-13-XX-10-0</b>  Solder mount in 2,59 min. mounting hole</p>
<p><b>8347</b>  <b>8347-0-15-XX-13-XX-10-0</b>  Solder mount in 2,77 min. mounting hole</p>	<p><b>4900</b>  <b>4900-0-19-XX-23-XX-10-0</b>  Swage mount in 1,70 hole</p>	<p><b>0716</b>  <b>0716-0-33-XX-23-XX-10-0</b>  Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.</p>	<p><b>0760</b>  <b>0760-0-18-XX-13-XX-10-0</b>  Press-fit in 2,69 mounting hole  For wire sizes up to 16 AWG</p>

**SPECIFICATIONS:**

**Shell Material:** Brass Alloy 360, 1/2 Hard  
**Contact Material:** Beryllium Copper Alloy 172, HT  
**Dimensions:** Millimeters  
**Tolerances On:** Lengths: ± 0,13  
Diameters: ± 0,051  
Angles: ± 2°



**ORDER CODE:** XXXX - X - XX - XX - XX - XX - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**

**#13 or #23 CONTACT (DATA ON PAGE 260)**  
(For alternate contact choices, see group G on page 248)

