

PIN RECEPTACLES

ZERO PROFILE SOLDERLESS PRESS-FIT RECEPTACLES (SEE SPECIFIC CONTACT RANGE ON PAGES 250 - 260)

<p>0621 0621-0-15-XX-04-XX-10-0 Recommended drilled hole size: 0,99mm (.039) #04 Contact for Ø 0,20 - 0,33 pins</p>	<p>0624 0624-0-15-XX-10-XX-10-0 Recommended drilled hole size: 1,25mm (.0492) #10 Contact for Ø 0,30 - 0,43 pins</p>	<p>0627 11or 0627-0-15-XX-21-XX-10-0 Recommended drilled hole size: 1,4mm (.0551) #11 Contact for Ø 0,38 - 0,51 pins #21 Contact for Ø 0,38 - 0,56 pins</p>	<p>0630 0630-0-15-XX-30-XX-10-0 Recommended drilled hole size: 1,75mm (.0689) #30 Contact for Ø 0,38 - 0,64 pins</p>
<p>0633 0633-0-15-XX-15-XX-10-0 Recommended drilled hole size: 1,85mm (.0728) #15 Contact for Ø 0,51 - 0,81 pins</p>	<p>0636 16or 0636-0-15-XX-47-XX-10-0 Recommended drilled hole size: 2mm (.0787) #16 For Ø 0,56 - 0,86 pins and 0,64 square #47 For Ø 0,64 - 0,94 pins and 0,64 square</p>	<p>0639 0639-0-15-XX-34-XX-10-0 Recommended drilled hole size: 2,3mm (.0906) #34 Contact for Ø 0,81 - 1,17 pins</p>	<p>0642 0642-0-15-XX-18-XX-10-0 Recommended drilled hole size: 2,3mm (.0906) #18 Contact for Ø 0,94 - 1,09 pins</p>
<p>0645 0645-0-15-XX-02-XX-10-0 Recommended drilled hole size: 2,55mm (.1004) #02 Contact for Ø 1,02 - 1,27 pins</p>	<p>0648 0648-0-15-XX-23-XX-10-0 Recommended drilled hole size: 3,15mm (.124) #23 Contact for Ø 1,14 - 1,65 pins</p>		

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Millimeters
Tolerances On: Lengths: ± 0,13
 Diameters: ± 0,51
 Angles: ± 2°



ORDER CODE: 06XX - X - 15 - XX - XX - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

SEE PART NUMBER FOR SPECIFIC CONTACT CALLOUT (Data on pages 250-260)
 (For alternate contact choices, see part number information)