













MALE PCB PINS

PRINTED CIRCUIT PINS • NAIL HEAD TYPE

<p>9050 9050-0-00-XX-00-00-33-0 Solder mount in .016 mounting hole</p> 	<p>4184 4184-0-00-XX-00-00-33-0 Solder mount in .014 mounting hole</p> 	<p>4825 4825-0-00-XX-00-00-33-0 Solder mount in .019 mounting hole Also available on 16mm wide carrier tape: 3,250 parts per 13" reel. See page 224.1 for Tape & Reel details</p> 	<p>4288 4288-0-00-XX-00-00-33-0 Solder mount in .022 mounting hole</p> 
<p>4353 4353-0-00-XX-00-00-33-0 Solder mount in .016 mounting hole Also available on 16mm wide carrier tape: 3,040 parts per 13" reel. See page 224.1 for Tape & Reel details</p> 	<p>4689 4689-0-00-XX-00-00-33-0 Solder mount in .019 mounting hole</p> 	<p>4068 4068-0-00-XX-00-00-33-0 Solder mount in .022 mounting hole Also available on 16mm wide carrier tape: 2,000 parts per 13" reel. See page 224.1 for Tape & Reel details</p> 	<p>5063 5063-0-00-XX-00-00-33-0 Solder mount in .024 mounting hole</p> 
<p>6547 6547-0-00-XX-00-00-33-0 Solder mount in .024 mounting hole Also available on 24mm wide carrier tape: 1,080 parts per 13" reel. See page 224.1 for Tape & Reel details</p> 	<p>9083 9083-0-00-XX-00-00-38-0 Solder mount in .016 mounting hole Also available on 16mm wide carrier tape: 1,950 parts per 13" reel. See page 224.1 for Tape & Reel details</p> 	<p>9185 9185-0-00-XX-00-00-33-0 Solder mount in .026 mounting hole</p> 	<p>8277 8277-0-00-XX-00-00-03-0 Solder mount in .026 mounting hole</p> 

SPECIFICATIONS:

Pin Material: Brass Alloy 360, 1/2 Hard
 (Except where noted)

Dimensions: Inches

Tolerances On: Lengths: $\pm .005$
 Diameters: $\pm .002$
 Angles: $\pm 2^\circ$



ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - XX - 0

BASIC PART # →

SPECIFY PIN FINISH:

- 01 200 μ " TIN/LEAD OVER NICKEL
- ◆ 80 200 μ " TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ " GOLD OVER NICKEL (RoHS)
- ◆ 21 20 μ " GOLD OVER NICKEL (RoHS)
- ◆ 34 50 μ " GOLD OVER NICKEL (RoHS)

