

PIN RECEPTACLES

FOR 0,56 - 0,86 DIAMETER PINS AND 0,64 SQUARE PINS

<p>0291 0291-0-15-XX-16-XX-10-0 Hex press-fit in 1,7 plated through-hole</p>	<p>0293 0293-0-15-XX-16-XX-10-0 Press-fit in 1,7 mounting hole</p>	<p>0287 0287-0-15-XX-16-XX-10-0 Solder mount in 1,65 min. mounting hole Also available on 8mm wide carrier tape: 3,250 parts per 330mm reel See page 194.11 for Tape & Reel details</p>	<p>0285 0285-0-15-XX-16-XX-10-0 Solder mount in 1,65 min. mounting hole</p>
<p>0284 0284-0-15-XX-16-XX-10-0 Solder mount in 1,78 min. mounting hole Also available on 24mm wide carrier tape: 1,200 parts per 330mm reel See page 194.11 for Tape & Reel details</p>	<p>8114 8114-0-15-XX-16-XX-04-0 Press-fit from underside of pc board into 1,65 mounting hole</p>	<p>0407 0407-0-15-XX-16-XX-04-0 Press-fit in 1,68 mounting hole</p>	<p>0415 0415-0-15-XX-16-XX-10-0 Solder mount in 1,6 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 330mm reel See page 194.11 for Tape & Reel details</p>
<p>0303 0303-0-19-XX-16-XX-10-0 Press-fit in 1,7 mounting hole Wire Crimp Termination. Accepts wire sizes 26 AWG Max. / 30 AWG Min.</p>	<p>0306 0306-0-19-XX-16-XX-10-0 Wire Crimp Termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>	<p>0273 0273-0-15-XX-16-XX-10-0 Press-fit in 1,98 mounting hole</p>	<p>7520 7520-0-15-XX-16-XX-10-0 Press-fit in 1,68 mounting hole</p>

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Millimeters

Tolerances On: Lengths: ± 0,13

Diameters: ± 0,051

Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - **16** - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,04µm TIN/LEAD OVER NICKEL
- ◆ 80 5,04µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,04µm TIN/LEAD OVER NICKEL
- ◆ 80 5,04µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#16 CONTACT (DATA ON PAGE 256)

(For alternate contact choices, see group D on page 248)

